B-frozen Smart 6



Professional equipment for preparing cold creams, sorbets, and granitas. Also available in the ETC version (Electronic Temperature Control).

Certifications








Available Voltages

230V 50Hz / 240V 50Hz / 115V 60Hz / 208-220V 60Hz / 100V 50-60Hz



Technical Specifications	B-frozen Smart 6.1	B-frozen Smart 6.2	B-frozen Smart 6.3
Capacity (L)	6	12	18
Height (cm)	62	62	62
Width (cm)	20	40	60
Depth (cm)	48	48	48
Net weight, approx. (Kg)	26	42 / 38 *	57
Gross weight, approx. (Kg)	28	45 / 41 *	61
Power * (W)	460	640	950
Gas (230V 50Hz)	R290	R290	R290
Gas (other voltages)	In compliance with current regulations, one of the following gases will be used: R1234ZE, R454C, R513a.		

^{*} Test conditions: 32°C - 230V 50Hz - 1st hour of operation

Additional Technical Features	Safety and control devices	
Shatterproof PETG (Tritan) container - BPA free	Noise level below 70 dB (A)	
Painted steel and ABS body	R290 gas models: equipped with ATEX electrical components	
Tilted container for easy emptying	Hermetic compressor with protector	
POM plastic stirrer	Mechanical product density control	
Air-cooled condenser	Accessible mechanical temperature control (115V only)	
Fixed-speed gear reducer	Pre-equipped for tap lock	
Patented magnetic transmission	Accessible and cleanable condenser air filter	
Lid unlocking button	Day/night function (production/maintenance mode)	
Tilted container for easy emptying	Internal electronic temperature control (230V only)	
Optional Accessories		
E-COAT: for energy savings and reduced condensation	Water-cooled condenser system (ETC version)	
Container/lid unlocking with key	Display (ETC version)	
Timer for day/night function	Product temperature display (ETC version)	
Illuminated cover	LED WALL: illuminated front display (LED technology)	
	Control panel (ETC version)	

Via Mario Ugolini, 3 - 27010 Torrevecchia Pia (PV) - Italia - +39 0382 1651 - <u>www.milanodispensers.com</u> - <u>www.brasmilano.com</u>