

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ



Warning

SECTION 1: identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Tetrafluoroethane (R134a)
SDS no : 00133_LIQ
Other means of identification : Tetrafluoroethane (R134a)
CAS-No. : 811-97-2
EC-No. : 212-377-0
EC Index-No. : ---
REACH registration No : 01-2119459374-33
Chemical formula : C₂H₂F₄

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.
Test gas/Calibration gas.
Chemical reaction / Synthesis.
Laboratory use.
Use as refrigerant.
Uses advised against : Consumer use.
Uses other than those listed above are not supported, contact your supplier for more information on other uses.

1.3. Details of the supplier of the safety data sheet

SIAD S.p.A.
Via San Bernardino, 92
I-24126 Bergamo – Italia
T +39 035 328111 - F +39 035 315486
siad_reach_clp@siad.com - www.siad.com

1.4. Emergency telephone number

Emergency telephone number : Linea verde S.E.T. - from Italy 800452661 - International +39 0362512868 - 24 hours a day, 365 days a year

Country	Organisation/Company	Address	Emergency number	Comment
Italy	Centro Antiveleni di Bergamo Azienda Ospedaliera Papa Giovanni XXII	Piazza OMS - Organizzazione Mondiale della Sanità, 1 24127 Bergamo	800 88 33 00	
Italy	Centro Antiveleni di Milano Ospedale Niguarda Ca' Granda	Piazza Ospedale Maggiore 3 20162 Milano	+39 02 6610 1029	
Italy	Centro Antiveleni di Roma CAV Policlinico "A. Gemelli", Dipartimento di Tossicologia Clinica Università Cattolica del Sacro Cuore	Largo Agostino Gemelli, 8 00168 Roma	+39 06 305 4343	

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

Italy	Centro Antiveleni di Roma CAV Policlinico "Umberto I", Università di Roma	Viale del Policlinico, 155 00161 Roma	+39 06 4997 8000
Italy	Centro Antiveleni di Firenze Az. Osp. "Careggi" U.O. Tossicologia Medica, S.O.D. di Tossicologia Clinica/cologia Clinica	Largo Brambilla, 3 50134 Firenze	+39 055 794 7819
Italy	Centro Antiveleni di Pavia CAV Centro Nazionale di Informazione Tossicologica, IRCCS Fondazione Maugeri	Via Salvatore Maugeri, 10 27100 Pavia	+39 03 822 4444
Italy	Centro Antiveleni di Roma CAV "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA	Piazza Sant'Onofrio, 4 00165 Roma	+39 06 6859 3726
Italy	Centro Antiveleni di Foggia Az. Osp. Univ. Foggia	V.le Luigi Pinto, 1 71122 Foggia	+39 800 183 459
Italy	Centro Antiveleni di Napoli Az. Osp. "A. Cardarelli"	Via A. Cardarelli, 9 80131 Napoli	+39 081 54 53 333
Italy	Centro Antiveleni di Verona Azienda Ospedaliera Integrata Verona	Piazzale Aristide Stefani, 1 37126 Verona	+39 800 011 858

SECTION 2: hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Gases under pressure : Liquefied gas	H280
------------------	--------------------------------------	------

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) : Warning

Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Storage : P403 - Store in a well-ventilated place.

Supplemental information : Contains fluorinated greenhouse gases listed in Annex I of EU 517/2014 as amended.

2.3. Other hazards

May be ignitable at higher pressure or temperature.
Asphyxiant in high concentrations.
Contact with liquid may cause cold burns/frostbite.
Not classified as PBT or vPvB.
The substance/mixture has no endocrine disrupting properties.

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

SECTION 3: composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 ICLP1
Tetrafluoroethane (R134a)	CAS-No.: 811-97-2 EC-No.: 212-377-0 EC Index-No.: --- REACH registration No: 01-2119459374-33	100	Press. Gas (Liq.), H280

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not applicable

SECTION 4: first aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.
See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Carbon monoxide. Hydrogen fluoride. Carbonyl fluoride.

5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Move containers away from the fire area if this can be done without risk.

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659 - Protective gloves for firefighters.

SECTION 6: accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Act in accordance with local emergency plan.
Try to stop release.
Evacuate area.
Ensure adequate air ventilation.
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Stay upwind.
See section 8 of the SDS for more information on personal protective equipment

For emergency responders : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Oxygen detectors should be used when asphyxiating gases may be released.
See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: handling and storage

7.1. Precautions for safe handling

Safe use of the product : The product must be handled in accordance with good industrial hygiene and safety procedures.
Only experienced and properly instructed persons should handle gases under pressure.
Consider pressure relief device(s) in gas installations.
Ensure the complete gas system was (or is regularly) checked for leaks before use.
Do not smoke while handling product.
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
Avoid suck back of water, acid and alkalis.
Do not breathe gas.
Avoid release of product into work area.

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.
Do not allow backfeed into the container.
Protect containers from physical damage; do not drag, roll, slide or drop.
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
If user experiences any difficulty operating valve discontinue use and contact supplier.
Never attempt to repair or modify container valves or safety relief devices.
Damaged valves should be reported immediately to the supplier.
Keep container valve outlets clean and free from contaminants particularly oil and water.
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
Close container valve after each use and when empty, even if still connected to equipment.
Never attempt to transfer gases from one cylinder/container to another.
Never use direct flame or electrical heating devices to raise the pressure of a container.
Do not remove or deface labels provided by the supplier for the identification of the content of the container.
Suck back of water into the container must be prevented.
Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.
Containers should not be stored in conditions likely to encourage corrosion.
Container valve guards or caps should be in place.
Containers should be stored in the vertical position and properly secured to prevent them from falling over.
Stored containers should be periodically checked for general condition and leakage.
Keep container below 50°C in a well ventilated place.
Store containers in location free from fire risk and away from sources of heat and ignition.
Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: exposure controls/personal protection

8.1. Control parameters

Tetrafluoroethane (R134a) (811-97-2)	
Austria - Occupational Exposure Limits	
Local name	1,1,1,2-Tetrafluoroethan (Norfluran)
MAK (mg/m ³)	4200 mg/m ³
MAK (OEL TWA) [ppm]	1000 ppm
MAK (OEL STEL)	16800 mg/m ³ (4x 15(Miw) min)
MAK (OEL STEL) [ppm]	4000 ppm (4x 15(Miw) min)
Regulatory reference	BGBl. II Nr. 382/2020
Croatia - Occupational Exposure Limits	
Local name	1,1,1,2-Tetrafluoroetan; norfluran
GVI (OEL TWA) [1]	4240 mg/m ³
GVI (OEL TWA) [2]	1000 ppm

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

Regulatory reference	Pravilnik o izmjenama i dopunama Pravilnika o graničnim vrijednostima izloženosti opasnim tvarima pri radu i o biološkim graničnim vrijednostima (NN 91/2018)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Norfluran
AGW (OEL TWA) [1]	4200 mg/m ³
AGW (OEL TWA) [2]	1000 ppm
Peak exposure limitation factor	8(II)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Lithuania - Occupational Exposure Limits	
Local name	1,1,1,2-tetrafluoretanas (HFC-134a, norfluranas)
IPRV (OEL TWA)	2000 mg/m ³
IPRV (OEL TWA) [ppm]	500 ppm
TPRV (OEL STEL)	3000 mg/m ³
TPRV (OEL STEL) [ppm]	750 ppm
Regulatory reference	LIETUVOS HIGIENOS NORMA HN 23:2011 (Nr. V-695/A1-272, 2018-06-12)
Slovenia - Occupational Exposure Limits	
Local name	norfluran
OEL TWA	4200 mg/m ³
OEL TWA [ppm]	1000 ppm
OEL STEL	33600 mg/m ³
OEL STEL [ppm]	8000 ppm
Remark	Y (Snovi, pri katerih ni nevarnosti za zarodek ob upoštevanju mejnih vrednosti in bat vrednosti)
Regulatory reference	Uradni list RS, št. 72/2021 z dne 11.5.2021
Sweden - Occupational Exposure Limits	
Local name	HFC 134 a (1,1,1,2-Tetrafluoretan)
NGV (OEL TWA)	2000 mg/m ³
NGV (OEL TWA) [ppm]	500 ppm
KTV (OEL STEL)	3000 mg/m ³
KTV (OEL STEL) [ppm]	750 ppm
Remark	V (Vägledande korttidsgränsvärde ska användas som ett rekommenderat högsta värde som inte bör överskridas)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)
United Kingdom - Occupational Exposure Limits	
Local name	1,1,1,2-Tetrafluoroethane (HFC 134a)
WEL TWA (OEL TWA) [1]	4240 mg/m ³
WEL TWA (OEL TWA) [2]	1000 ppm
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

North Macedonia - Occupational Exposure Limits

Local name	Норфлуран
OEL TWA	4200 mg/m ³
OEL TWA [ppm]	1000 ppm
KTV	4
Short time value [mg/m ³]	16800 mg/m ³
Short time value [ppm]	4000 ppm
Remark	(KTV) краткотрајна вредност (КТВ) значи концентрација на опасни хемиски супстанции во воздухот на работното место внатре во зона на дишење, на која работникот без опасност по здравјето може да е изложен на покусо време. Изложеноста на краткотрајни вредности може да трае највеќе 15 минути и не смее да се повтори повеќе од четирипати во работната смена, при што меѓу две изложености на оваа концентрација мора да измине најмалку 60 минути. Краткотрајната вредност е изразена во mg/m ³ или во ml/m ³ (ppm) а е дадена како многукратни дозволени пречекорувања на граничната вредност; (Y)
Regulatory reference	Правилник за минималните барања за безбедност и здравје при работа на вработени од ризици поврзани со изложување на хемиски супстанции („Службен весник на Република Македонија“ бр.46/10)

Switzerland - Occupational Exposure Limits

Local name	1,1,1,2-Tetrafluoroethane / 1,1,1,2-Tetrafluorethan [Tetrafluorethan]
MAK (OEL TWA) [1]	4200 mg/m ³
MAK (OEL TWA) [2]	1000 ppm
Critical toxicity	Formel / Formal
Notation	SS _c / SS _c
Regulatory reference	www.suva.ch, 01.01.2021

Tetrafluoroethane (R134a) (811-97-2)

DNEL: Derived no effect level (Workers)

Long-term - systemic effects, inhalation	13936 mg/m ³
--	-------------------------

Tetrafluoroethane (R134a) (811-97-2)

PNEC: Predicted no effect concentration

Aqua (freshwater)	0.1 mg/l
Aqua (marine water)	0.01 mg/l
Aquatic, intermittent releases	1 mg/l
Sediment, freshwater	0.75 mg/kg dwt
Micro-organisms in sewage treatment plant (STP)	73 mg/l

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Oxygen detectors should be used when asphyxiating gases may be released.
Consider the use of a work permit system e.g. for maintenance activities.

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

8.2.2. Individual protection measures, e.g. personal protective equipment

- A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:
- PPE compliant to the recommended EN/ISO standards should be selected.
- Eye/face protection
 - : Wear goggles when transfilling or breaking transfer connections.
 - Standard EN 166 - Personal eye-protection - specifications.
 - Skin protection
 - Hand protection
 - : Wear working gloves when handling gas containers.
 - Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
 - Wear cold insulating gloves when transfilling or breaking transfer connections.
 - Standard EN 511 - Cold insulating gloves.
 - Other
 - : Wear safety shoes while handling containers.
 - Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
 - Respiratory protection
 - : Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
 - Consult respiratory device supplier's product information for the selection of the appropriate device.
 - Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.
 - Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
 - Thermal hazards
 - : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas
- Colour	: Colourless.
Odour	: Ethereal.
	Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: -101 °C
Boiling point	: -26.1 °C
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: May be ignitable at higher pressure or temperature
Explosive limits	: Non flammable.
Lower explosive limit (LEL)	: Not applicable.
Upper explosive limit (UEL)	: Not applicable.
Vapour pressure [20°C]	: 4.7 bar(a)
Vapour pressure [50°C]	: 13.2 bar(a)
Density and/or relative density	: Not applicable for gases and gas mixtures.
Relative vapour density (air=1)	: 3.6
Water solubility	: 1930 mg/l
Partition coefficient n-octanol/water (Log Kow)	: 0.94
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: Not applicable for gases and gas mixtures.
Particle characteristics	: Not applicable for gases and gas mixtures.
	Nanoforms are not relevant for gases and gas mixtures

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Oxidising properties : No oxidising properties.

Critical temperature [°C] : 101 °C

9.2.2. Other safety characteristics

Molar mass : 102 g/mol

Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

Moisture.

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Classification criteria are not met.

LC50 Inhalation - Rat [ppm] 567000 ppm/4h

Skin corrosion/irritation : No known effects from this product.

Serious eye damage/irritation : No known effects from this product.

Respiratory or skin sensitisation : No known effects from this product.

Germ cell mutagenicity : No known effects from this product.

Carcinogenicity : No known effects from this product.

Toxic for reproduction : Fertility : No known effects from this product.

Toxic for reproduction : unborn child : No known effects from this product.

STOT-single exposure : No known effects from this product.

STOT-repeated exposure : No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

SECTION 12: ecological information

12.1. Toxicity

Assessment	: Classification criteria are not met.
EC50 48h - Daphnia magna [mg/l]	: 930 mg/l
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: 450 mg/l

12.2. Persistence and degradability

Assessment	: Not readily biodegradable.
------------	------------------------------

12.3. Bioaccumulative potential

Assessment	: See section 9. Not expected to bioaccumulate due to the low log Kow (log Kow < 4).
------------	---

12.4. Mobility in soil

Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
------------	---

12.5. Results of PBT and vPvB assessment

Assessment	: Not classified as PBT or vPvB.
------------	----------------------------------

12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: No effect on the ozone layer.
Global warming potential [CO ₂ =1]	: 1430
Effect on global warming	: When discharged in large quantities may contribute to the greenhouse effect. Contains fluorinated greenhouse gases listed in Annex I of EU 517/2014 as amended. For quantities refer to cylinder label.

SECTION 13: disposal considerations

13.1. Waste treatment methods

	Contact supplier if guidance is required. Discharge to atmosphere in large quantities should be avoided. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.eu for more guidance on suitable disposal methods. Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 14 06 01 *: Chlorofluorocarbons, HCFC, HFC.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

SECTION 14: transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 3159

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : 1,1,1,2-TETRAFLUOROETHANE (REFRIGERANT GAS R 134a)

Transport by air (ICAO-TI / IATA-DGR) : Refrigerant gas R 134a

Transport by sea (IMDG) : 1,1,1,2-TETRAFLUOROETHANE (REFRIGERANT GAS R 134a)

14.3. Transport hazard class(es)

Labelling



2.2 : Non-flammable, non-toxic gases.

Transport by road/rail (ADR/RID)

Class : 2

Classification code : 2A

Hazard identification number : 20

Tunnel Restriction : C/E - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2

Emergency Schedule (EmS) - Fire : F-C

Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not applicable

Transport by air (ICAO-TI / IATA-DGR) : Not applicable

Transport by sea (IMDG) : Not applicable

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 200.

Cargo Aircraft only : 200.

Transport by sea (IMDG) : P200

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.
-------------------------------	---

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use	: None. Contains no substance(s) listed on the REACH Candidate List.
Other information, restriction and prohibition regulations	: (EC) No 517/2014 : on fluorinated greenhouse gases and repealing Regulation (EC) No 842/2006. Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals). Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants).
Seveso Directive : 2012/18/EU (Seveso III)	: Not covered.

National regulations

Regulatory reference	: Ensure all national/local regulations are observed.
----------------------	---

15.2. Chemical safety assessment

A CSA has been carried out.

SECTION 16: other information

Indication of changes	: Safety data sheet in accordance with commission regulation (EU) No 2020/878.
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 EINECS - European Inventory of Existing Commercial Chemical Substances CAS# - Chemical Abstract Service number PPE - Personal Protection Equipment LC50 - Lethal Concentration to 50 % of a test population RMM - Risk Management Measures PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative STOT SE - Specific Target Organ Toxicity - Single Exposure CSA - Chemical Safety Assessment EN - European Standard UN - United Nations ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road

Safety Data Sheet

Tetrafluoroethane (R134a)

SDS reference: 00133_LIQ

<p>Training advice</p>	<p>IATA - International Air Transport Association IMDG code - International Maritime Dangerous Goods RID - Regulations concerning the International Carriage of Dangerous Goods by Rail STOT RE - Specific Target Organ Toxicity - Repeated Exposure UFI - Unique Formula Identifier</p> <p>: The hazard of asphyxiation is often overlooked and must be stressed during operator training.</p> <p>For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu.</p>
<p>Further information</p>	<p>: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).</p> <p>Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu.</p>
<p>Full text of H- and EUH-statements</p> <p>H280</p> <p>Press. Gas (Liq.)</p>	<p>Contains gas under pressure; may explode if heated.</p> <p>Gases under pressure : Liquefied gas</p>
<p>DISCLAIMER OF LIABILITY</p>	<p>: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.</p> <p>Details given in this document are believed to be correct at the time of going to press.</p> <p>Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.</p> <p style="text-align: right;">End of document</p>